

64K CMOS Static RAM (8192×8) 28PIN 6264

型 名	社 名	温度範囲 (℃)	ス イ ッ チ ン グ 特 性										電 源		入 力 [・typ]			出 力 [・typ]				備 考
			TAAC max (ns)	TCAC max (ns)	T0E max (ns)	T0H min (ns)	T0D max (ns)	TWP min (ns)	TDS min (ns)	T0H min (ns)	TWD min (ns)	TWR max (ns)	VDD or VCC (V)	ID0 max (mA)	ID0 STANDBY (1SB/1SB2) (mA)	VIL max (V)	VIH min (V)	Ci max (pF)	VOL/1VOL max (V/mA)	VOH/1VOH min (V/mA)	Co max (pF)	
MSM5165-20RS	OKI	0~70	200		100	20	60	120	80	0	0		4.5~5.5	45		3/1	0.8	2.2	6	0.4/2.1	2.4/1	8
MSM5165L-12RS	OKI	0~70	120		60	10	40	70	50	0	0		4.5~5.5	45		3/0.1	0.8	2.2	6	0.4/2.1	2.4/1	8
MSM5165L-15RS	OKI	0~70	150		70	15	50	90	60	0	0		4.5~5.5	45		3/0.1	0.8	2.2	6	0.4/2.1	2.4/1	8
MSM5165L-20RS	OKI	0~70	200		100	20	60	120	80	0	0		4.5~5.5	45		3/0.1	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164-10	NS	0~70	100		50	35		60		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164-12	NS	0~70	120		60	40		70		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164-15	NS	0~70	150		70	50		90		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164L-10	NS	0~70	100		50	35		60		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164L-12	NS	0~70	120		60	40		70		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
NMC6164L-15	NS	0~70	150		70	50		90		0	0		4.5~5.5	25		4/-	0.8	2.2	6	0.4/2.1	2.4/1	8
P4C164-20	PFM		20		10	2	8	15	11	0	0		4.5~5.5	110		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164-25	PFM		25		13	3	10	18	13	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164-30	PFM		30		15	3	13	20	15	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164-35	PFM		35		18	3	15	20	15	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164-45	PFM		45		20	3	20	25	20	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164L-20	PFM		20		10	2	8	15	11	0	0		4.5~5.5	110		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164L-25	PFM		25		13	3	10	18	13	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164L-30	PFM		30		15	3	13	20	15	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164L-35	PFM		35		18	3	15	20	15	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
P4C164L-45	PFM		45		20	3	20	25	20	0	0		4.5~5.5	90		21/-	0.8	2.2	5	0.4/8	2.4/4	7
SR64K8-40	LATTICE		40		20	5	25	30	15	0	0		4.5~5.5	170		40/-	0.8	2.2	5	0.4/8	2.4/4	7
SR64K8-45	LATTICE		45		25	5	25	35	20	0	0		4.5~5.5	170		40/-	0.8	2.2	5	0.4/8	2.4/4	7
SR64K8-55	LATTICE		55		30	5	25	40	30	0	0		4.5~5.5	170		40/-	0.8	2.2	5	0.4/8	2.4/4	7
SR64K8-70	LATTICE		70		35	5	30	55	30	0	0		4.5~5.5	170		40/-	0.8	2.2	5	0.4/8	2.4/4	7
SRM2064C12	SEIKO	0~70	120		60	30	60	80	50	0			4.5~5.5	45		3/0.1	0.8	2.2	7	0.4/4	2.4/1	8
SRM2064C15	SEIKO	0~70	150		70	30	70	100	60	0			4.5~5.5	40		3/0.1	0.8	2.2	7	0.4/4	2.4/1	8
SRM2264LC10	SEIKO	0~70	100		50	10	35	60	50	0	0		4.5~5.5	82		1/0.02	0.8	2.2	6	0.4/4	2.4/1	7
SRM2264LC12	SEIKO	0~70	120		60	10	40	70	50	0	0		4.5~5.5	80		1/0.02	0.8	2.2	6	0.4/4	2.4/1	7
SRM2264LC90	SEIKO	0~70	90		50	10	35	60	50	0	0		4.5~5.5	85		1/0.02	0.8	2.2	6	0.4/4	2.4/1	7
TC5588BP/J-10	TOSHIBA	-10~85	10	10	6	3	5	6	6	0		1	4.75~5.25	155		30/10	0.8	2.2	5	0.4/-	4/2.4	7
TC5588BP/J-12	TOSHIBA	-10~85	12	12	7	3	6	7	7	0		1	4.5~5.5	155		30/10	0.8	2.2	5	0.4/-	4/2.4	7
TC5564LP-10	TOSHIBA	-30~85	100		50	30	50	70	40	0	0		4.5~5.5	45	2/0.0002							
TC5564LP-15	TOSHIBA	-30~85	150		70	30	70	100	60	0	0		4.5~5.5	45	2/0.0002							
TC5564P-10	TOSHIBA	-30~85	100		50	30	50	70	40	0	0		4.5~5.5	45	2/0.02	0.8	2.0	5	0.4/4	2.4/1	7	
TC5564P-15	TOSHIBA	-30~85	150		70	30	70	100	60	0	0		4.5~5.5	45	2/0.02	0.8	2.0	5	0.4/4	2.4/1	7	
TC5565FL-12L	TOSHIBA	0~70	120		60	10	60	80		0	0		4.5~5.5	45	3/0.03	0.8	2.2	10	0.4/4	2.4/1	10	
TC5565FL-15L	TOSHIBA	0~70	150		70	10	70	100		0	0		4.5~5.5	45	3/0.03	0.8	2.2	10	0.4/4	2.4/1	10	
TC5565LP-12	TOSHIBA	0~70	120		60		60	80	50				4.5~5.5	45	3/0.1							
TC5565LP-15	TOSHIBA	0~70	150		70		70	100	60				4.5~5.5	45	3/0.1							
TC5565P-12	TOSHIBA	0~70	120		60	20	60	80	50	0	0		4.5~5.5	45	3/1	0.8	2.0	10	0.4/4	2.4/1	10	
TC5565P-15	TOSHIBA	0~70	150		70	20	70	100	60	0	0		4.5~5.5	45	3/1	0.8	2.0	10	0.4/4	2.4/1	10	
TC5565PL-12L	TOSHIBA	0~70	120		60	10	60	80		0	0		4.5~5.5	45	3/0.03	0.8	2.2	10	0.4/4	2.4/1	10	