




Ultra High Precision Foil Wraparound Surface Mount Chip Resistor with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$ and Power Coefficient of 5 ppm at Rated Power



Top View

Any value at any tolerance within resistance range

INTRODUCTION

VSMP Series is the industry's first device to provide High Rated power, Excellent load life stability along with extremely low TCR all in one resistor.

One of the most important parameters influencing stability is the Temperature Coefficient of Resistance (TCR). Although the TCR of foil resistors is considered extremely low, this characteristic has been further refined over the years. The VSMP Series utilizes ultra high precision Bulk Metal® Z-Foil. The Z-Foil technology provides a significant reduction of the resistive element's sensitivity to ambient temperature variations (TCR) and to self heating when power is applied (power coefficient). Along with the inherently low PCR and TCR, Z-Foil technology also provides remarkably improved load life stability, low noise and availability of tight tolerance.

The VSMP has a full wraparound termination which ensures safe handling during the manufacturing process, as well as providing stability during multiple thermal cyclings.

Our Application Engineering Department is available to advise and make recommendations. For non-standard technical requirements and special applications, please contact us using the e-mail address in the footer below.

TABLE 1 - TOLERANCE AND TCR VS RESISTANCE VALUE ¹⁾ (- 55 °C to + 125 °C, + 25 °C Ref.)		
RESISTANCE VALUE (Ω)	TOLERANCE (%)	TYPICAL TCR AND MAX. SPREAD (ppm/°C)
250 to 150K	± 0.01	± 0.2 ± 1.8
100 to < 250	± 0.02	± 0.2 ± 1.8
50 to < 100	± 0.05	± 0.2 ± 2.8
25 to < 50	± 0.1	± 0.2 ± 3.8
10 to < 25	± 0.25	± 0.2 ± 3.8

Note

1. For tighter performances, please contact Vishay Application Engineering using the e-mail addresses in the footer below.

* Pb containing terminations are not RoHS compliant, exemptions may apply

FEATURES


- Temperature Coefficient of Resistance (TCR): 0.05 ppm/°C typical (0 °C to + 60 °C)
0.2 ppm/°C typical (- 55 °C to + 125 °C, + 25 °C Ref.)
- Tolerance: to ± 0.01 %
- Power Coefficient "ΔR due to self heating": 5 ppm at Rated Power
- Power Rating: to 750 mW at + 70 °C
- Load Life Stability: to ± 0.005 % at 70 °C, 2000 hours at Rated Power
- Resistance Range: 10 Ω to 150 kΩ (for higher and lower values, please contact us)
- Electrostatic Discharge (ESD) above 25 000 Volts
- Short Time Overload: ≤ 0.005 %
- Non Inductive, Non Capacitive Design
- Rise Time: 1 ns without ringing
- Current Noise: - 40 dB
- Voltage Coefficient < 0.1 ppm/V
- Non Inductive: < 0.08 μH
- Non Hot Spot Design
- Terminal Finishes Available: Lead (Pb)-free Tin/Lead Alloy
- Matched sets are available on request
- Any value available within resistance range (e.g. 1K2345)
- Prototype samples available from 48 hours. For more information, please contact foil@vishay.com
- For better performances please contact us



APPLICATIONS

- Automatic Test Equipment (ATE)
- High Precision Instrumentation
- Laboratory, Industrial and Medical
- Audio
- EB Applications (electron beam scanning and recording equipment, electron microscopes)
- Military and Space
- Airborne
- Down Hole instrumentation
- Communication



FIGURE 1 - POWER DERATING CURVE



VSMP Series (0805, 1206, 1506, 2010, 2512) (Z-Foil)



Vishay Foil Resistors Ultra High Precision Foil Wraparound Surface Mount Chip Resistor with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$ and Power Coefficient of 5 ppm at Rated Power



Note
• The TCR values for $< 100 \Omega$ are influenced by the termination composition and result in deviation from this curve.

TABLE 2 - DIMENSIONS AND LAND PATTERN in inches (millimeters)

Bottom View for Mounting

Recommended Land Pattern

CHIP SIZE	L ± 0.005 (0.13)	W ± 0.005 (0.13)	THICKNESS MAXIMUM	D ± 0.005 (0.13)	Z ¹⁾ MAXIMUM	G ¹⁾ MINIMUM	X ¹⁾ MAXIMUM
0805	0.080 (2.03)	0.050 (1.27)	0.025 (0.64)	0.015 (0.38)	0.122 (3.10)	0.028 (0.71)	0.050 (1.27)
1206	0.126 (3.20)	0.062 (1.57)	0.025 (0.64)	0.020 (0.51)	0.175 (4.45)	0.059 (1.50)	0.071 (1.80)
1506	0.150 (3.81)	0.062 (1.57)	0.025 (0.64)	0.020 (0.51)	0.199 (5.05)	0.083 (2.11)	0.071 (1.80)
2010	0.198 (5.03)	0.097 (2.46)	0.025 (0.64)	0.025 (0.64)	0.247 (6.27)	0.115 (2.92)	0.103 (2.62)
2512	0.249 (6.32)	0.127 (3.23)	0.025 (0.64)	0.032 (0.81)	0.291 (7.39)	0.150 (3.81)	0.127 (3.23)

Note
1. Land Pattern Dimensions are per IPC-782

TABLE 3 - SPECIFICATIONS

CHIP SIZE	RATED POWER (mW) at +70 °C	MAX VOLTAGE RATING ($\leq \sqrt{P \times R}$)	RESISTANCE RANGE (Ω)	MAXIMUM WEIGHT (mg)
0805	200	49 V	10 to 12K	6
1206	300	95 V	10 to 30K	11
1506	300	110 V	10 to 40K	12
2010	500	200 V	10 to 100K	27
2512	750	220 V	10 to 150K	40

TABLE 4 - LOAD LIFE STABILITY
(+70 °C for 2000 hours)

CHIP SIZE	MAXIMUM ΔR LIMITS
0805	$\pm 0.005\%$ at 100 mW $\pm 0.01\%$ at 200 mW
1206, 1506	$\pm 0.005\%$ at 150 mW $\pm 0.01\%$ at 300 mW
2010	$\pm 0.005\%$ at 200 mW $\pm 0.01\%$ at 500 mW
2512	$\pm 0.005\%$ at 500 mW $\pm 0.01\%$ at 750 mW

TABLE 5 - PERFORMANCES

TEST OR CONDITIONS	MIL-PRF-55342 CHARACTERISTIC E ΔR LIMITS	TYPICAL ΔR LIMITS	MAXIMUM ΔR LIMITS ¹⁾
Thermal Shock	$\pm 0.1\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.01\%$ (100 ppm)
Low Temperature Operation	$\pm 0.1\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.01\%$ (100 ppm)
Short Time Overload	$\pm 0.1\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.01\%$ (100 ppm)
High Temperature Exposure	$\pm 0.1\%$	$\pm 0.01\%$ (100 ppm)	$\pm 0.02\%$ (200 ppm)
Resistance to Soldering Heat	$\pm 0.2\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.01\%$ (100 ppm)
Moisture Resistance	$\pm 0.2\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.02\%$ (200 ppm)
Load Life Stability +70 °C for 2000 hours at Rated Power	$\pm 0.5\%$	$\pm 0.005\%$ (50 ppm)	$\pm 0.01\%$ (100 ppm)

Note
1. As shown +0.01 Ω to allow for measurement errors at low values.



VSMP Series (0805, 1206, 1506, 2010, 2512) (Z-Foil)

Ultra High Precision Foil Wraparound Surface Mount Chip Resistor with TCR of $\pm 0.05 \text{ ppm}/^\circ\text{C}$ and Power Coefficient of 5 ppm at Rated Power

FIGURE 4 - RECOMMENDED MOUNTING




TABLE 6 - DSCC SPECIFICATIONS

Vishay resistors are listed on the following DSCC specifications


MODEL	DSCC	MIL SPEC
VSMP1506	03010	MIL-PRF-55342
VSMP2010	06001	MIL-PRF-55342
VSMP2512	06002	MIL-PRF-55342

Note

- For VSMP0805 and VSMP1206 DSCC drawings, please contact foil@vishay.com

TABLE 7 - GLOBAL PART NUMBER INFORMATION

NEW GLOBAL PART NUMBER: Y162612K7560T9R (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y1626 12K7560 T 9 R:

TYPE: VSMP1506
VALUES: 12.7560 $k\Omega$
ABSOLUTE TOLERANCE: 0.01 %
TERMINATION: Lead (Pb)-free
PACKAGING: Tape and Reel

HISTORICAL PART NUMBER: VSMP1506 12K756 TCR0.2 T S T (will continue to be used)

VSMP1506	12K756	TCR0.2	T	S	T
MODEL	RESISTANCE VALUE	TCR CHARACTERISTICS	TOLERANCE	TERMINATION	PACKAGING
VSMP0805 VSMP1206 VSMP1506 VSMP2010 VSMP2512	12.756 $k\Omega$		T = $\pm 0.01 \%$ Q = $\pm 0.02 \%$ A = $\pm 0.05 \%$ B = $\pm 0.10 \%$ C = $\pm 0.25 \%$ D = $\pm 0.5 \%$ F = $\pm 1.0 \%$	S = Lead (Pb)-free B = Tin/Lead	T = Tape and Reel W = Waffle Pack

Note

* For non-standard requests, please contact Application Engineering.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.