

ALPS Detector Switches



HIS compliant This page of product is compliant.

ALPS SMD LOW-PROFILE ONE-WAY DETECTOR SWITCHES

Features:


Highly reliable double-sided sliding contact
Tape and reel packaging

Specifications:

Rating: 1mA @ 5VDC
Operating life with load: 50,000 cycles

Applications: Detection mechanism in video cameras

- Detection mechanism in DVD players
- RoHS Compliant



ALPS SMD LOW-PROFILE TWO-WAY DETECTOR SWITCHES

Features:

Specifications:

Rating: 1mA @ 5VDC
Operating life with load: 50,000 cycles · Can be pressed horizontally, vertically or at an angle. · Ultra thin - only 1mm high · Total travel position: 1.45mm Tape and reel packaging ON starting position, horizontal: 1.95mm Applications

Detection of covers on mobile phones, PDAs
Detection mechanism in DVD players

· Detection mechanism in portable CD/MD players

* ON starting position in	vertical direction	For quar	ntities of 10,0	000 and up, c	all for quote					
MOUSER	Alps		OF	Control	ON Start	Location		Price	Each	
STOCK NO.	Part Number	Fig.		Direction	Position *	Lug	1	50	100	500
688-SPVN110101	SPVN110101	В	35 gf	Right	2.65 mm	Yes	1.16	1.00	.91	.66
688-SPVN120101	SPVN120101	В	35 gf	Right	3.46 mm	No	1.16	1.00	.91	.66
688-SPVN210101	SPVN210101	C	35 gf	Left	2.65 mm	Yes	1.16	1.00	.91	.66
688-SPVN220101	SPVN220101	С	35 gf	Left	3.46 mm	No	1.16	1.00	.91	.66

ALPS SMD COMPACT TWO-WAY DETECTOR SWITCHES

Features:

Specifications: Rating: 1mA @ 5VDC

horizontally and vertically Tape and reel packaging

· Can be pressed from 2 directions -

- Operating life with load: 50,000 cycles
 Total travel position: 1.5mm
- Detection of covers on mobile phones, PDAs · Detection mechanism in DVD players

							For qua	antities of 45	00 and up, c	all for quote.
MOUSER	Alps	Fig. OF Haveing		ON Start Location		Price Each				
STOCK NO.	Part Number	Fig.	OF	Housing	Position	Lug	1	50	100	500
688-SPVM110100	SPVM110100	D	40 gf	w/o terminal	2.20 mm	Yes	.86	.74	.68	.49
688-SPVM110200	SPVM110200	D	40 gf	w/ terminal	2.20 mm	No	.86	.74	.68	.49

ALPS SMD TWO-WAY DETECTOR SWITCHES

ALPS Features:

Can be pressed horizontally, vertically or at an angle Tape and reel packaging **Detection Switches**

Specifications: Rating: 50mA @ 20VDC Operating life with load: 100,000 cycles
 Location Lug

RoHS Compliant Applications: Detection of lids on laptops, mobile phones, and PDAs · Detection of position of camera shutters in mobile phones

	For quantities of 5000 and up, call for quot													
MOUSER	Alps	_	05	Control	ON Start	Side		Price	Each					
STOCK NO.	Part Number	Fig.	OF	Direction	ection Position	Terminal	1	50	100	500				
688-SPVG110301	SPVG110301	Е	40 gf	Right	2.96 mm	Yes	.79	.58	.51	.38				
688-SPVG120302	SPVG120302	E	40 gf	Right	2.96 mm	No	.79	.58	.51	.38				
688-SPVG210302	SPVG210302	F	40 gf	Left	2.96 mm	Yes	.79	.58	.51	.38				
688-SPVG220300	SPVG220300	F	40 gf	Left	2.96 mm	No	.79	.58	.51	.38				
688-SPVG310300	SPVG310300	E	40 gf	Right	2.45 mm	Yes	.79	.58	.51	.38				
688-SPVG320200	SPVG320200	E	40 gf	Right	2.45 mm	No	.79	.58	.51	.38				
688-SPVG410300	SPVG410300	F	40 gf	Left	2.45 mm	Yes	.79	.58	.51	.38				
688-SPVG420200	SPVG420200	F	40 gf	Left	2.45 mm	No	.79	.58	.51	.38				

ALPS SMD LOW-PROFILE TRI-DIRECTIONAL DETECTOR SWITCHES

Specifications:

Specifications:

Features

Applications:

· World's smallest detector switch of its type · Highly reliable double-sided sliding contact

· Tape and reel packaging

Rating: 1mA @ 5VDC
Operating life with load: 50,000 cycles

 Detection mechanism in PDAs, mobile 0 phones, car audio Detection functions in DSCs RoHS Compliant for quote.

For q	uantities	of	7500	and	up,	call	1
	_						

MOUSER	Alps	E:n	05	ON Start	Total Travel	Location		Price	Each	
STOCK NO.	Part Number	Fig.	OF	Position	Position	Lug	1	50	100	500
688-SPVL110100	SPVL110100	G	35 gf	4.25 mm	3.75 mm	Yes	1.28	1.10	1.01	.73
688-SPVL120100	SPVL120100	G	35 gf	4.25 mm	3.75 mm	No	1.28	1.10	1.01	.73

ALPS SMD COMPACT DETECTOR SWITCHES

Features:

· World's smallest detector switch of its type

- Highly reliable double-sided sliding contact
- · Tape and reel packaging
- Rating: 100mA @ 12VDC
- SPVE1xxx have location lug, SPVE2xxx do not
 Operating life with load: 50,000 cycles
 - · Detection of lid position in laptops and mobile phones · Detection of media in CD/MD players


Applications:

For quantities	grea	ater	than	listed,	call	for	quote	١.
	-		-					ı.


Mouser Catalog Download

Detection of batteries in LCDs and DSCs


							For quanti	ties greater	han listed, c	all for quot	
MOUSER	Alps		g. OF	Dim.	ON Start Position	Total Travel	Price Each				
STOCK NO.	Part Number	Fig.		"H"		Position	1	50	100	500	
688-SPVE110600	SPVE110600	н	30 gf	3.80 mm	3.50 mm	2.50 mm	.79	.57	.52	.40	
688-SPVE110801	SPVE110801	н	30 gf	4.10 mm	3.80 mm	2.90 mm	.79	.57	.52	.40	
688-SPVE110900	SPVE110900	н	30 gf	4.80 mm	4.50 mm	3.60 mm	.79	.57	.52	.40	
688-SPVE210100	SPVE210100	1	30 gf	3.30 mm	3.00 mm	2.00 mm	.79	.57	.52	.40	
688-SPVE210200	SPVE210200	1	30 gf	4.75 mm	4.45 mm	3.35 mm	.79	.57	.52	.40	
© Copyright 2007 Mouser Electronics											




5.65




Shown w/side terminal



Shown w/side terminal







www.DataSheet4U.com









RoHS Compliant

Applications:

5

в **RoHS** Compliant

F

 G

 $\left| \mathsf{H} \right\rangle$

 $| \rangle$

a

NEXT DIMENSIONS: mm

