



Specification:

Material:

Insulator: PBT, rated UL94V-0

Contacts: Brass

Shell: Steel

Rivet, Boardlock: Copper Alloy

Contact Plating:

Gold Flash over 50u"nickel

Electrical

Operation Voltage: 250 VAC max.

Current Rating: 3 Amps max.

Contact Resistance: 15 mohms max.

Insulation Resistance: 3000 Mohms min @ 500 VDC

Dielectric Withstanding Voltage: 1000 VAC/minute

Operating Temperature: -55°C to +105°C

| Position | A | B | C | D |
|----------|-------|-------|------|------|
| 9F | 16.30 | 25.00 | 30.8 | 19.2 |
| 15F | 24.60 | 33.30 | 39.2 | 27.7 |
| 19F | 30.00 | 38.86 | 44.8 | 32.8 |
| 23F | 35.30 | 44.30 | 50.3 | 38.3 |
| 25F | 38.30 | 47.10 | 53.1 | 41.1 |
| 37F | 54.80 | 63.50 | 69.4 | 57.3 |

| Description | |
|---|--|
| Name : A-DFXXPP-TAXM-B D-Sub Solder | |
| | |



THIS DRAWING IS UNPUBLISHED
© Copyright 2005 by Assmann Electronic Components All International Rights Reserved
This drawing is a controlled document for Assmann Electronics, Inc. It is subject to change and the controlling engineering organization should be contacted for the latest revision.