

Materials

Pin (outer sleeve) : Brass, machined, CuZn38Pb2
Clip (contact 4 finger) : Beryllium copper, heat treated or PHBZ
Plating (outer sleeve) : Tin plated : $2\mu\text{m}/80\mu\text{''}$ nickel, $5\mu\text{m}/200\mu\text{''}$ Tin
Plating clip (contact): $2\mu\text{m}/80\mu\text{''}$ nickel, full gold
Insulator body (black) : Glass filled thermoplastic polyester UL94V-0





Electrical

Current rating : 3 Amps/contact max.
Contact resistance : Max $4\text{m}\Omega$
Insulation resistance : Min $10,000\text{m}\Omega$ @ 500 V AC
Operating Voltage : 100 VRMS / 150 V AC

Mechanical

Operating temperature : Tin plated: -40°C to $+105^\circ\text{C}$
Average insertion force with steel pin of: $0.43\text{mm}/0.017\text{''}$ <250g
Average withdrawal force with steel pin of: $0.43\text{mm}/0.017\text{''}$ >50g
Mechanical life : min.200

Packaging: Tube



P.C.B. LAYOUT

RoHS
Compliant

ITEM NO

AR14-HZL-TT-R

TITLE IC-Socket, 14Pin, Machined Contacts,
Pitch: 2.54MM, Pin Length: 7.43MM

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2009 by Assmann Electronic Components
All International Rights Reserved

Find price and stock options from leading distributors for AR14-HZL-TT-R on Findchips.com:

<https://findchips.com/search/AR14-HZL-TT-R>

Find CAD models and details for this part:

<https://findchips.com/detail/ar14-hzl-tt-r/ASSMANN-WSW-components-GmbH>