

Product: <u>9221</u> ☑

Analog Video, #30 Str TC, 90% TC Braid, PVC Jacket



Product Description

30 AWG stranded (7x38) .012" tinned copper conductor, foam HDPE insulation, tinned copper braid shield (90% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor									
AWG	S Stranding Material		Nominal Diameter	No. of Coax					
30	Stranded TC - Tinned Copper 0.01		0.012 in	1					
Condu	ctor Count:				1				
nsulat	ion								
	Material		Nominal Dia	meter					
PE - P	olyethylene (Foam)	0.058 in						
Outer S	Shield								
_	Materi	iol	Coverage	2/1					
Туре			Coverage [70]					
Braid	Tinned Cop	per (TC)	90%						
Outer J	Jacket								
Material Nominal Diameter									
PVC - Polyvinyl Chloride 0.097 in									
Electrical Characteristics									
Conductor DCR									
Non	ninal Condu DCR	ctor	Nominal Cor	nductor DCR Condu	ictor Resistanc	Nominal Outer Shield DCR	Outer Conductor D		
100 O	100 Ohm/1000ft 100 Ohm/1000ft				11.65 Ohm/1000ft	11.65 Ohm/1000ft			

Capacitance

Nom. Capacitance Conductor to SI	nield
17.3 pF/ft	

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance 75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss	
1 MHz	0.7 dB/100ft	
3.6 MHz	1.3 dB/100ft	

5 MHz	1.6 dB/100ft		
7 MHz	1.9 dB/100ft		
9 MHz	2.1 dB/100ft		
10 MHz	2.2 dB/100ft		
50 MHz	5.1 dB/100ft		
70 MHz	6.1 dB/100ft		
100 MHz	7.3 dB/100ft		
200 MHz	10.5 dB/100ft		
400 MHz	15.5 dB/100ft		
700 MHz	21.5 dB/100ft		
900 MHz	24.8 dB/100ft		
1000 MHz	26.6 dB/100ft		

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	78%

Voltage

UL Voltage Rating 30 V RMS

Temperature Range

UL Temp Rating:	60°C
Operating Temperature Range:	-40°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	6 lbs/1000ft
Max. Pull Tension:	14 lbs
Min. Bend Radius/Minor Axis:	0.25 in

Standards

UL AWM Style Compliance:	AWM 1375 (30 V 60°C)	
CPR Euroclass:	Eca	
RG Type:	Ultra-miniature 59	

Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

IEC 60332-1-2				
30 V RMS				
Plenum/Non-Plenum				
Plenum (Y/N): No				

UPC

Related Part Numbers

Item #

9221 010100	Black	Reel	100 ft	612825358848
9221 010500	Black	Reel	500 ft	612825358152
9221 010U500	Black	UnReel	500 ft	612825358862

History

Update and Revision:

Revision Number: 0.327 Revision Date: 11-09-2022

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.