


CL-170 シリーズ

Miniature Chip LED CL-170 Series ■ Ultra Small Size



2.0(L)×1.25(W)×1.1(H)mm

● 外形寸法は2.0(L)×1.25(W)×1.1(H)mmの小型タイプです。

● Dimensions:2.0(L)×1.25(W)×1.1(H)mm, being small size

●絶対最大定格/Absolute Maximum Rating

(Ta 25°C)

Series	Pd (mW)	I _F (mA)	I _{FP} (mA)	V _R (V)	T _{op} (°C)	T _{st} (°C)
CL-170 (UR,HRを除く Except UR and HR)	65	25	100*1	5	-25~+80	-30~+85
CL-170UR/HR	78	30				

*1 I_{FP}の条件はduty 1/10、パルス巾0.1msecです。

*1 Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

●電氣的光学的特性/Electro-optical Characteristics



(Ta 25°C)

Code for parts	Lighting color	V _F			λ _p typ (nm)	Δλ typ (nm)	I _v * (mcd)		
		I _F (mA)	typ (V)	max (V)			I _F (mA)	min (mcd)	typ (mcd)
CL-170R	Red	20	2.2	2.6	700	100	20	0.5	1.3
CL-170D	Orange	20	2.2	2.6	605	40	20	2.4	7.1
CL-170Y	Yellow	20	2.1	2.6	589	40	20	2.6	6.4
CL-170YG	Yellow green	20	2.2	2.6	570	30	20	5	18
CL-170G	Green	20	2.2	2.6	567	26	20	2.5	10
CL-170FG	Fresh green	20	2.2	2.6	560	26	20	2.2	6.5
CL-170PG	Pure green	20	2.2	2.6	557	24	20	1	3
CL-170SR	Super brightness red	20	2	2.6	650	40	20	1.5	4.3
CL-170SD	Super brightness orange	20	2	2.6	630	40	20	2	6.2
CL-170UR	Ultra brightness red	20	1.8	2.6	660	20	20	3.5	13
CL-170HR	High brightness red	20	1.8	2.6	660	20	20	5	23

*NIST規格に準拠

*Per NIST standards

●外形寸法図/Outline drawing



■ 諸特性 / Characteristics

