

Non-Metallic Sheathed Cable Connectors

Clamp, Set Screw & Duplex Type



CLAMP TYPE – STEEL

UL File No. E-22132



Clamp Opening

Cat. #	K.O. Size	Min.	Max.	Width	Unit Qty.	Wt. Lbs. Per 100
631	3/4"	33/64"	13/16"	13/16"	20	14
			For 2 conductor No.'s 8, 6 3 conductor No.'s 8, 6			
632	1"	3/8"	1 1/64"	1 1/64"	10	21
			For 2 conductor No.'s 8, 6 3 conductor No.'s 8, 6			

CLAMP TYPE – ZINC DIE CAST

UL File No. E-302794



Cat. #	Trade Size	K.O. Size	Unit Qty.	Wt. Lbs. Per 100
759DC	3/8"	1/2"	100	4
			For 2 conductor No.'s 14, 12, 10 3 conductor No.'s 14, 12	
2631	3/4"	3/4"	50	9
			For 3 conductor No.'s 8, 6	
2632	1"	1"	25	12
			For 3 conductor No.'s 6, 4	
2633	1 1/4"	1 1/4"	10	22
			For 3 conductor No.'s 3, 2	
2670	1 1/2"	1 1/2"	5	25
			For 3 conductor No. 2 / 0	
2671	2"	2"	10	40
			For 3 conductor No. 4 / 0	

SET SCREW TYPE - ZINC DIE CAST

UL File No. E-19188



Cat. #	Trade Size	Diam. of Opening for Cable	Diam. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
ACB38DC	3/8"			50	35

DUPLEX TYPE – ZINC DIE CAST

UL File No. E-19188



Cat. #	Trade Size	Diam. of Opening for Cable	Diam. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
2699*	3/8"	5/8"	9/16"	25	13

*UL Listed as grounding means.

NM Sheathed