

■ Type List for Chip Type Aluminum Electrolytic Capacitors

★ : New product series

☆ : Extension product series

○ : Circle symbols apply to those capacitors with rated voltage of 250V or less.

Category	Series	Page	Applications	Feature								Category Temp Range °C		Rated Voltage Range V. DC		Rated Capacitance Range μF		Color of sleeve	JIS Configuration	Note	
				Thin and small size	Reliability at 105°C					Low Impedance	For Audio										Anti-cleaning solvent
					1000 hrs	2000 hrs	3000 hrs	5000 hrs	10000 hrs			Max	Min	Max	Min						
Surface Mount	RV2	23	5.5mm L	●								●	●	85	-40	50	4	0.1 to 220	Silver	32	
	RV	24	Higher Capacitance Range									●	●	85	-40	100	6.3	10 to 1000	Silver Brown	32	
	RV	25	Large size, Higher Capacitance Range									●	●	85	-40	100	6.3	100 to 3300	Brown	32	
	RV3	26	High CV	●								●	●	85	-40	50	6.3	4.7 to 330	Silver	32	
	RV4	27	4.5mm L	●								●	●	85	-40	50	6.3	0.1 to 100	Silver	32	
	★RV5	28	High CV	●								●	●	85	-40	100	6.3	2.2 to 1500	Silver Brown	32	
	RVB	30	Non Polarized	●								●	●	85	-40	50	6.3	0.1 to 47	Silver	32	
	RVS	31	105°C, 5.5mm L	●	●							●	●	105	-55	50	6.3	0.1 to 100	Silver	32	
	RVL	32	Long Life, 105°C, 6.0mm L	●		●						●	●	105	-55	50	6.3	0.1 to 100	Silver	32	
	RVJ	33	105°C, Higher Capacitance			●						●	●	105	-55	100	6.3	10 to 1000	Silver Brown	32	
	RVJ	34	105°C, Large size, Higher Capacitance Range				●					●	●	105	-55	100	6.3	47 to 1000	Brown	32	
	RVH	35	105°C, Low Impedance			●				●		●	●	105	-55	35	6.3	47 to 470	Brown	32	
	RVZ	36	105°C, Low Impedance			●				●		●	●	105	-55	35	6.3	4.7 to 1500	Silver Brown	32	
	RVK	38	125°C, Higher Reliability				●					●	●	125	-40	63	10	10 to 330	Brown	32	
	RVK	39	125°C, Large size, Higher Capacitance Range					●				●	●	125	-40	6.3	10	100 to 1000	Brown	32	
	RT	40	Higher Capacitance, Vibration resistance			●						●	●	85	-40	100	6.3	10 to 1000	Brown	32	
	RTJ	41	105°C, Higher Capacitance, Vibration resistance			●				●		●	●	105	-55	100	6.3	10 to 470	Brown	32	
	RTH	42	105°C, Low Impedance, Vibration resistance			●						●	●	105	-55	35	6.3	47 to 470	Brown	32	
RTK	43	125°C, Vibration resistance				●					●	●	125	-40	63	10	10 to 330	Brown	32		
RYK	44	125°C, Horizontal type				●							125	-40	63	6.3	56 to 820	Black	32		

* Be sure to review "Cautions for Using Aluminum Electrolytic Capacitors", before using these products.

*1 Please refer to our web-page about RJJ series and L3J series. (web-address <http://www.elna.co.jp/>)

*2 There are overseas factory product only on above table.

Note:

- (1) Design, Specifications are subject to change without notice.
- (2) Ask factory for technical specifications before purchase and/or use.