80MHz, 25V/µs Low Power Rail-to-Rail Input and Output Precision Op Amp

FEATURES

- **Gain Bandwidth Product: 80MHz**
- **Input Common Mode Range Includes Both Rails**
- **Output Swings Rail-to-Rail**
- **Low Quiescent Current: 2mA Max**
- **Input Offset Voltage: 350µV Max**
- **Input Bias Current: 250nA Max**
- Low Voltage Noise: 8.5nV/√Hz
- Slew Rate: 25V/µs
- Common Mode Rejection: 105dB
- Power Supply Rejection: 97dB
- Open-Loop Gain: 85V/mV
- Operating Temperature Range: –40°C to 85°C
- Available in the 8-Pin SO and 5-Pin Low Profile (1mm) ThinSOT™ Packages

APPLICATIONS

- Low Voltage, High Frequency Signal Processing
- Driving A/D Converters
- Rail-to-Rail Buffer Amplifiers
- Active Filters
- Video Line Driver

DESCRIPTION

The LT®1800 is a low power, high speed rail-to-rail input and output operational amplifier with excellent DC performance. The LT1800 features reduced supply current, lower input offset voltage, lower input bias current and higher DC gain than other devices with comparable bandwidth.

The LT1800 has an input range that includes both supply rails and an output that swings within 20mV of either supply rail to maximize the signal dynamic range in low supply applications.


The LT1800 maintains its performance for supplies from 2.3V to 12.6V and is specified at 3V, 5V and ±5V supplies. The inputs can be driven beyond the supplies without damage or phase reversal of the output.

The LT1800 is available in the 8-pin SO package with the standard op amp pinout and in the 5-pin TSOT-23 package. For dual and quad versions of the LT1800, see the LT1801/LT1802 data sheet. The LT1800 can be used as a plug-in replacement for many op amps to improve input/output range and performance.


LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. ThinSOT is a trademark of Linear Technology Corporation. All other trademarks are the property of their respective owners.

TYPICAL APPLICATION

Single Supply 1A Laser Driver Amplifier




Laser Driver Amplifier 500mA Pulse Response



ABSOLUTE MAXIMUM RATINGS (Note 1)


Total Supply Voltage (V_S^- to V_S^+) 12.6V
Input Current (Note 2).....±10mA
Output Short-Circuit Duration (Note 3) ..... Indefinite
Operating Temperature Range (Note 4)....–40°C to 85°C
Specified Temperature Range (Note 5) ....–40°C to 85°C
Junction Temperature ..... 150°C
Storage Temperature Range.....–65°C to 150°C
Lead Temperature (Soldering, 10 sec)..... 300°C

PIN CONFIGURATION



S8 PACKAGE
8-LEAD PLASTIC SO

T_{JMAX} = 150°C, θ_{JA} = 190°C/W



S5 PACKAGE
5-LEAD PLASTIC TSOT-23

T_{JMAX} = 150°C, θ_{JA} = 250°C/W

ORDER INFORMATION

LEAD FREE FINISH	TAPE AND REEL	PART MARKING	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE
LT1800CS8#PBF	LT1800CS8#TRPBF	1800	8-Lead Plastic SO	0°C to 70°C
LT1800IS8#PBF	LT1800IS8#TRPBF	1800I	8-Lead Plastic SO	–40°C to 85°C
LT1800CS5#PBF	LT1800CS5#TRPBF	LTRN	5-Lead Plastic TSOT-23	0°C to 70°C
LT1800IS5#PBF	LT1800IS5#TRPBF	LTRP	5-Lead Plastic TSOT-23	–40°C to 85°C

Consult LTC Marketing for parts specified with wider operating temperature ranges.
Consult LTC Marketing for information on non-standard lead based finish parts.

For more information on lead free part marking, go to: http://www.linear.com/leadfree/
For more information on tape and reel specifications, go to: http://www.linear.com/tapeandreel/

ELECTRICAL CHARACTERISTICS

T_A = 25°C. V_S = 5V, 0V; V_S = 3V, 0V; V_{CM} = V_{OUT} = half supply, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	V_{CM} = 0V V_{CM} = 0V (SOT-23) V_{CM} = V_S V_{CM} = V_S (SOT-23)		75 300 0.5 0.7	350 750 3 3.5	µV µV mV mV
ΔV_{OS}	Input Offset Shift	V_{CM} = 0V to V_S – 1.5V		20	180	µV
I_B	Input Bias Current	V_{CM} = 1V V_{CM} = V_S		25 500	250 1500	nA nA
I_{OS}	Input Offset Current	V_{CM} = 1V V_{CM} = V_S		25 25	200 200	nA nA
	Input Noise Voltage	0.1Hz to 10Hz		1.4		μV_{P-P}

ELECTRICAL CHARACTERISTICS

T_A = 25°C. V_S = 5V, 0V; V_S = 3V, 0V; V_{CM} = V_{OUT} = half supply, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
e_n	Input Noise Voltage Density	f = 10kHz		8.5		nV/√Hz
i_n	Input Noise Current Density	f = 10kHz		1		pA/√Hz
C_{IN}	Input Capacitance	f = 100kHz		2		pF
A_{VOL}	Large-Signal Voltage Gain	V_S = 5V, V_O = 0.5V to 4.5V, R_L = 1k at V_S/2 V_S = 5V, V_O = 1V to 4V, R_L = 100Ω at V_S/2 V_S = 3V, V_O = 0.5V to 2.5V, R_L = 1k at V_S/2	35 3.5 30	85 8 85		V/mV V/mV V/mV
CMRR	Common Mode Rejection Ratio	V_S = 5V, V_{CM} = 0V to 3.5V V_S = 3V, V_{CM} = 0V to 1.5V	85 78	105 97		dB dB
	Input Common Mode Range		0		V_S	V
PSRR	Power Supply Rejection Ratio	V_S = 2.5V to 10V, V_{CM} = 0V	80	97		dB
	Minimum Supply Voltage (Note 6)			2.3	2.5	V
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 20mA		12 80 225	50 160 450	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 20mA		16 120 450	60 250 850	mV mV mV
I_{SC}	Short-Circuit Current	V_S = 5V V_S = 3V	20 20	45 40		mA mA
I_S	Supply Current per Amplifier			1.6	2	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz	40	80		MHz
SR	Slew Rate	V_S = 5V, A_V = –1, R_L = 1k, V_O = 4V	13	25		V/µs
FPBW	Full Power Bandwidth	V_S = 5V, V_{OUT} = $4V_{P-P}$		2		MHz
HD	Harmonic Distortion	V_S = 5V, A_V = 1, R_L = 1k, V_O = $2V_{P-P}$, f_C = 500kHz		–75		dBc
t_S	Settling Time	0.01%, V_S = 5V, V_{STEP} = 2V, A_V = 1, R_L = 1k		250		ns
ΔG	Differential Gain (NTSC)	V_S = 5V, A_V = +2, R_L = 150Ω		0.35		%
Δθ	Differential Phase (NTSC)	V_S = 5V, A_V = +2, R_L = 150Ω		0.4		Deg

The ● denotes the specifications which apply over the temperature range of 0°C ≤ T_A ≤ 70°C. V_S = 5V, 0V; V_S = 3V, 0V; V_{CM} = V_{OUT} = half supply, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	V_{CM} = 0V V_{CM} = 0V (SOT-23) V_{CM} = V_S V_{CM} = V_S (SOT-23)	● ● ● ●		125 300 0.6 0.7	500 1250 3.5 3.75	µV µV mV mV
$ΔV_{OS}$	Input Offset Shift	V_{CM} = 0V to V_S – 1.5V	●		30	275	µV
V_{OS} TC	Input Offset Voltage Drift (Note 8)		●		1.5	5	µV/°C
I_B	Input Bias Current	V_{CM} = 1V V_{CM}= V_S – 0.2V	● ●		50 550	300 1750	nA nA
I_{OS}	Input Offset Current	V_{CM} = 1V V_{CM} = V_S – 0.2V	● ●		25 25	250 250	nA nA
A_{VOL}	Large-Signal Voltage Gain	V_S = 5V, V_O = 0.5V to 4.5V, R_L = 1k at V_S/2 V_S = 5V, V_O = 1V to 4V, R_L = 100Ω at V_S/2 V_S = 3V, V_O = 0.5V to 2.5V, R_L = 1k at V_S/2	● ● ●	30 3 25	75 6 75		V/mV V/mV V/mV
CMRR	Common Mode Rejection Ratio	V_S = 5V, V_{CM} = 0V to 3.5V V_S = 3V, V_{CM} = 0V to 1.5V	● ●	82 74	101 93		dB dB

ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the temperature range of 0°C ≤ T_A ≤ 70°C. C. V_S = 5V, 0V; V_S = 3V, 0V; V_{CM} = V_{OUT} = half supply, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
	Input Common Mode Range		●	0		V_S	V
PSRR	Power Supply Rejection Ratio	V_S = 2.5V to 10V, V_{CM} = 0V	●	74	91		dB
	Minimum Supply Voltage (Note 6)		●		2.3	2.5	V
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 20mA	● ● ●		14 100 300	60 200 550	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 20mA	● ● ●		25 150 600	80 300 1000	mV mV mV
I_{SC}	Short-Circuit Current	V_S = 5V V_S = 3V	● ●	20 20	40 30		mA mA
I_S	Supply Current per Amplifier		●		2	2.75	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz	●	35	75		MHz
SR	Slew Rate	V_S = 5V, A_V = – 1, R_L = 1k, V_O = 4V_{P-P}	●	11	22		V/µs

The ● denotes the specifications which apply over the temperature range of –40°C ≤ T_A ≤ 85°C. V_S = 5V, 0V; V_S = 3V, 0V; V_{CM} = V_{OUT} = half supply, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	V_{CM} = 0V V_{CM} = 0V (SOT-23) V_{CM} = V_S V_{CM} = V_S (SOT-23)	● ● ● ●		175 400 0.75 0.9	700 2000 4 4	µV µV mV mV
ΔV_{OS}	Input Offset Shift	V_{CM} = 0V to V_S – 1.5V	●		30	300	µV
V_{OS} TC	Input Offset Voltage Drift (Note 8)		●		1.5	5	µV/°C
I_B	Input Bias Current	V_{CM} = 1V V_{CM} = V_S – 0.2V	● ●		50 600	400 2000	nA nA
I_{OS}	Input Offset Current	V_{CM} = 1V V_{CM} = V_S – 0.2V	● ●		25 25	300 300	nA nA
A_{VOL}	Large-Signal Voltage Gain	V_S = 5V, V_O = 0.5V to 4.5V, R_L = 1k at V_S/2 V_S = 5V, V_O = 1.5V to 3.5V, R_L = 100Ω at V_S/2 V_S = 3V, V_O = 0.5V to 2.5V, R_L = 1k at V_S/2	● ● ●	25 2.5 20	65 6 65		V/mV V/mV V/mV
CMRR	Common Mode Rejection Ratio	V_S = 5V, V_{CM} = 0V to 3.5V V_S = 3V, V_{CM} = 0V to 1.5V	● ●	81 73	101 93		dB dB
	Input Common Mode Range		●	0		V_S	V
PSRR	Power Supply Rejection Ratio	V_S = 2.5V to 10V, V_{CM} = 0V	●	73	90		dB
	Minimum Supply Voltage (Note 6)		●		2.3	2.5	V
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 10mA	● ● ●		15 105 170	70 210 400	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 10mA	● ● ●		25 150 300	90 350 700	mV mV mV
I_{SC}	Short-Circuit Current	V_S = 5V V_S = 3V	● ●	12.5 12.5	30 30		mA mA
I_S	Supply Current per Amplifier		●		2.1	3	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz	●	30	70		MHz
SR	Slew Rate	V_S = 5V, A_V = – 1, R_L = 1k, V_O = 4V	●	10	18		V/µs

ELECTRICAL CHARACTERISTICS

T_A = 25°C, V_S = ±5V, V_{CM} = 0V, V_{OUT} = 0V, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	$V_{CM} = V_S^-$ $V_{CM} = V_S^-$ (SOT-23) $V_{CM} = V_S^+$ $V_{CM} = V_S^+$ (SOT-23)		150 400 0.7 1	500 1000 3.5 4.5	µV µV mV mV
ΔV_{OS}	Input Offset Shift	$V_{CM} = V_S^-$ to $V_S^+ – 1.5V$		30	475	µV
I_B	Input Bias Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S^+$		25 400	350 1500	nA nA
I_{OS}	Input Offset Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S^+$		20 20	250 250	nA nA
	Input Noise Voltage	0.1Hz to 10Hz		1.4		μV_{P-P}
e_n	Input Noise Voltage Density	f = 10kHz		8.5		$nV/\sqrt{Hz}$
i_n	Input Noise Current Density	f = 10kHz		1		$pA/\sqrt{Hz}$
C_{IN}	Input Capacitance	f = 100kHz		2		pF
A_{VOL}	Large-Signal Voltage Gain	V_O = –4V to 4V, R_L = 1k V_O = –2V to 2V, R_L = 100Ω	25 2.5	70 7		V/mV V/mV
CMRR	Common Mode Rejection Ratio	$V_{CM} = V_S^-$ to 3.5V	85	109		dB
	Input Common Mode Range		V_S^-		V_S^+	V
PSRR	Power Supply Rejection Ratio	V_S^+ = 2.5V to 10V, V_S^- = 0V	80	97		dB
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 20mA		15 85 225	60 170 450	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 20mA		17 130 450	70 260 900	mV mV mV
I_{SC}	Short-Circuit Current		30	50		mA
I_S	Supply Current per Amplifier			1.8	2.75	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz		70		MHz
SR	Slew Rate	A_V = – 1, R_L = 1k, V_O = ±4V, Measured at V_O = ±2V		23		V/µs
FPBW	Full Power Bandwidth	$V_O = 8V_{P-P}$		0.9		MHz
HD	Harmonic Distortion	A_V = 1, R_L = 1k, $V_O = 2V_{P-P}$, f_C = 500kHz		–75		dBc
t_S	Settling Time	0.01%, V_{STEP} = 5V, A_V = 1V, R_L = 1k		300		ns
ΔG	Differential Gain (NTSC)	A_V = + 2, R_L = 150Ω		0.35		%
$\Delta\theta$	Differential Phase (NTSC)	A_V = + 2, R_L = 150Ω		0.2		Deg

The ● denotes the specifications which apply over the temperature range of 0°C ≤ T_A ≤ 70°C. V_S = ±5V, V_{CM} = 0V, V_{OUT} = 0V, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	$V_{CM} = V_S^-$ $V_{CM} = V_S^-$ (SOT-23) $V_{CM} = V_S^+$ $V_{CM} = V_S^+$ (SOT-23)	● ● ● ●		200 450 0.75 1	800 1500 4 5	µV µV mV mV
ΔV_{OS}	Input Offset Shift	$V_{CM} = V_S^-$ to $V_S^+ – 1.5V$	●		45	675	µV
V_{OS} TC	Input Offset Voltage Drift (Note 8)		●		1.5	5	µV/°C
I_B	Input Bias Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S^+ – 0.2V$	● ●		30 450	400 1750	nA nA

ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the temperature range of 0°C ≤ T_A ≤ 70°C. V_S = ±5V, V_{CM} = 0V, V_{OUT} = 0V, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
I_{OS}	Input Offset Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S^+ - 0.2V$	● ●		25 25	300 300	nA nA
A_{VOL}	Large-Signal Voltage Gain	V_O = –4V to 4V, R_L = 1k V_O = –2V to 2V, R_L = 100Ω	● ●	20 2	55 5		V/mV V/mV
CMRR	Common Mode Rejection Ratio	$V_{CM} = V_S^-$ to 3.5V	●	82	105		dB
	Input Common Mode Range		●	V_S^-		V_S^+	V
PSRR	Power Supply Rejection Ratio	V_S^+ = 2.5V to 10V, V_S^- = 0V	●	74	91		dB
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 20mA	● ● ●		17 105 250	70 210 575	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 20mA	● ● ●		25 150 600	90 310 1100	mV mV mV
I_{SC}	Short-Circuit Current		●	25	45		mA
I_S	Supply Current per Amplifier		●		2.4	3.5	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz	●		70		MHz
SR	Slew Rate	A_V = –1, R_L = 1k, V_O = ±4V, Measured at V_O = ±2V	●		20		V/µs

The ● denotes the specifications which apply over the temperature range of –40°C ≤ T_A ≤ 85°C. V_S = ±5V, V_{CM} = 0V, V_{OUT} = 0V, unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
V_{OS}	Input Offset Voltage	$V_{CM} = V_S^-$ $V_{CM} = V_S^-$ (SOT-23) $V_{CM} = V_S$+ $V_{CM} = V_S$+ (SOT-23)	● ● ● ●		350 500 0.75 1	900 2250 4.5 5.5	µV µV mV mV
ΔV_{OS}	Input Offset Shift	$V_{CM} = V_S^-$ to V_S^+ – 1.5V	●		50	750	µV
V_{OS} TC	Input Offset Voltage Drift (Note 8)		●		1.5	5	µV/°C
I_B	Input Bias Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S$+ – 0.2V	● ●		50 450	450 2000	nA nA
I_{OS}	Input Offset Current	$V_{CM} = V_S^- + 1V$ $V_{CM} = V_S$+ – 0.2V	● ●		25 25	350 350	nA nA
A_{VOL}	Large-Signal Voltage Gain	V_O = –4V to 4V, R_L = 1k V_O = –1V to 1V, R_L = 100Ω	● ●	16 2	55 5		V/mV V/mV
CMRR	Common Mode Rejection Ratio	$V_{CM} = V_S^-$ to 3.5V	●	81	104		dB
	Input Common Mode Range		●	V_S^-		V_S^+	V
PSRR	Power Supply Rejection Ratio	V_S^+ = 2.5V to 10V, V_S^- = 0V	●	73	90		dB
V_{OL}	Output Voltage Swing Low (Note 7)	No Load I_{SINK} = 5mA I_{SINK} = 10mA	● ● ●		15 105 170	80 220 400	mV mV mV
V_{OH}	Output Voltage Swing High (Note 7)	No Load I_{SOURCE} = 5mA I_{SOURCE} = 10mA	● ● ●		25 150 300	100 350 700	mV mV mV
I_{SC}	Short-Circuit Current		●	12.5	30		mA
I_S	Supply Current per Amplifier		●		2.6	4	mA
GBW	Gain Bandwidth Product	Frequency = 2MHz	●		65		MHz
SR	Slew Rate	A_V = –1, R_L = 1k, V_O = ±4V, Measured at V_O = ±2V	●		15		V/µs

ELECTRICAL CHARACTERISTICS

Note 1: Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

Note 2: The inputs are protected by back-to-back diodes and by ESD diodes to the supply rails. If the differential input voltage exceeds 1.4V or either input goes outside the rails, the input current should be limited to less than 10mA.

Note 3: A heat sink may be required to keep the junction temperature below the absolute maximum rating when the output is shorted indefinitely.

Note 4: The LT1800C/LT1800I are guaranteed functional over the temperature range of –40°C to 85°C.

Note 5: The LT1800C is guaranteed to meet specified performance from 0°C to 70°C. The LT1800C is designed, characterized and expected to meet specified performance from –40°C to 85°C but is not tested or QA sampled at these temperatures. The LT1800I is guaranteed to meet specified performance from –40°C to 85°C.


Note 6: Minimum supply voltage is guaranteed by power supply rejection ratio test.

Note 7: Output voltage swings are measured between the output and power supply rails.


Note 8: This parameter is not 100% tested.

TYPICAL PERFORMANCE CHARACTERISTICS


V_{OS} Distribution, V_{CM} = 0V (SO-8, PNP Stage)




V_{OS} Distribution, V_{CM} = 5V (SO-8, NPN Stage)




V_{OS} Distribution, V_{CM} = 0V (SOT-23, PNP Stage)




V_{OS} Distribution, V_{CM} = 5V (SOT-23, NPN Stage)



Supply Current vs Supply Voltage




Offset Voltage vs Input Common Mode Voltage




TYPICAL PERFORMANCE CHARACTERISTICS

Input Bias Current vs Common Mode Voltage




1800 G07

Input Bias Current vs Temperature




1800 G08

Output Saturation Voltage vs Load Current (Output Low)




1800 G09

Output Saturation Voltage vs Load Current (Output High)




1800 G10

Minimum Supply Voltage




1800 G11

Output Short-Circuit Current vs Power Supply Voltage




1800 G12

Open-Loop Gain




1800 G13

Open-Loop Gain



1800 G14


Open-Loop Gain



1800 G15


TYPICAL PERFORMANCE CHARACTERISTICS

Offset Voltage vs Output Current




1800 G16

Warm-Up Drift vs Time (LT1800S8)




1800 G17

Input Noise Voltage vs Frequency




1800 G18

Input Current Noise vs Frequency




1800 G19

0.1Hz to 10Hz Output Voltage Noise




1800 G20

Gain Bandwidth and Phase Margin vs Supply Voltage



1800 G21


Gain Bandwidth and Phase Margin vs Temperature



1800 G22


TYPICAL PERFORMANCE CHARACTERISTICS

Slew Rate vs Temperature




1800 G23

Gain and Phase vs Frequency




1800 G24

Gain vs Frequency (A_V = 1)




1800 G25

Gain vs Frequency (A_V = 2)




1800 G26

Output Impedance vs Frequency




1800 G27

Common Mode Rejection Ratio vs Frequency




1800 G28

Power Supply Rejection Ratio vs Frequency



1800 G29


Series Output Resistor vs Capacitive Load



1800 G30


TYPICAL PERFORMANCE CHARACTERISTICS

Series Output Resistor vs Capacitive Load




1800 G31

Distortion vs Frequency




1800 G32

Distortion vs Frequency




1800 G33

Maximum Undistorted Output Signal vs Frequency



1800 G34


5V Large-Signal Response



1800 G35

VS = 5V, 0V 100ns/DIV
AV = 1
RL = 1k


5V Small-Signal Response



1800 G36

VS = 5V, 0V 50ns/DIV
AV = 1
RL = 1k


±5V Large-Signal Response



1800 G37

VS = ±5V 200ns/DIV
AV = 1
RL = 1k


±5V Small-Signal Response



1800 G38

VS = ±5V 50ns/DIV
AV = 1
RL = 1k

Output Overdriven Recovery



1800 G39

VS = 5V, 0V 100ns/DIV
AV = 2
RL = 1k

APPLICATIONS INFORMATION

Circuit Description

The LT1800 has an input and output signal range that covers from the negative power supply to the positive power supply. Figure 1 depicts a simplified schematic of the amplifier. The input stage is comprised of two differential amplifiers, a PNP stage Q1/Q2 and an NPN stage Q3/Q4 that are active over the different ranges of common mode input voltage. The PNP differential pair is active between the negative supply to approximately 1.2V below the positive supply. As the input voltage moves closer toward the positive supply, the transistor Q5 will steer the tail current I_1 to the current mirror Q6/Q7, activating the NPN differential pair and the PNP pair becomes inactive for the rest of the input common mode range up to the positive supply. Also at the input stage, devices Q17 to Q19 act to cancel the bias current of the PNP input pair. When Q1-Q2 are active, the current in Q16 is controlled to be the same as the current in Q1-Q2, thus the base current of Q16 is nominally equal to the base current of the input devices. The base current of Q16 is then mirrored by devices Q17-Q19 to cancel the base current of the input devices Q1-Q2.

A pair of complementary common emitter stages Q14/Q15 that enable the output to swing from rail to rail constructs the output stage. The capacitors C2 and C3 form the local feedback loops that lower the output impedance at high frequency. These devices are fabricated on Linear Technology's proprietary high speed complementary bipolar process.

Power Dissipation

The LT1800 amplifier is offered in a small package, SOT-23, which has a thermal resistance of 250°C/W, θ_{JA}. So there is a need to ensure that the die's junction temperature should not exceed 150°C. Junction temperature T_J is calculated from the ambient temperature T_A, power dissipation P_D and thermal resistance θ_{JA}:

$$T_J = T_A + (P_D \bullet \theta_{JA})$$

The power dissipation in the IC is the function of the supply voltage, output voltage and the load resistance. For a given supply voltage, the worst-case power dissipation P_{DMAX} occurs at the maximum supply current and the




Figure 1. LT1800 Simplified Schematic Diagram

APPLICATIONS INFORMATION

output voltage is at half of either supply voltage (or the maximum swing is less than 1/2 supply voltage). P_{DMAX} is given by:

$$P_{DMAX} = (V_S \bullet I_{SMAX}) + (V_S/2)^2/R_L$$

Example: An LT1800 in a SOT-23 package operating on ±5V supplies and driving a 50Ω load, the worst-case power dissipation is given by:

$$P_{DMAX} = (10 \bullet 4mA) + (2.5)^2/50 = 0.04 + 0.125 = 0.165W$$

The maximum ambient temperature that the part is allowed to operate is:

$$T_A = T_J - (P_{DMAX} \bullet 250°C/W)$$
$$= 150°C - (0.165W \bullet 250°C/W) = 108°C$$

Input Offset Voltage

The offset voltage will change depending upon which input stage is active. The PNP input stage is active from the negative supply rail to 1.2V of the positive supply rail, then the NPN input stage is activated for the remaining input range up to the positive supply rail during which the PNP stage remains inactive. The offset voltage is typically less than 75μV in the range that the PNP input stage is active.

Input Bias Current

The LT1800 employs a patent-pending technique to trim the input bias current to less than 250nA for the input common mode voltage of 0.2V above negative supply rail to 1.2V of the positive rail. The low input offset voltage and low input bias current of the LT1800 provide the precision performance especially for high source impedance applications.

Output

The LT1800 can deliver a large output current, so the short-circuit current limit is set around 50mA to prevent damage to the device. Attention must be paid to keep the junction temperature of the IC below the absolute maximum rating of 150°C (refer to the Power Dissipation section) when the output is continuously short-circuited. The output of the amplifier has reverse-biased diodes connected to each supply. If the output is forced beyond either supply, unlimited current will flow through these diodes. If the current is transient and limited to several hundred mA, and the total supply voltage is less than 12.6V, the absolute maximum rating, no damage will occur to the device.

Overdrive Protection

When the input voltage exceeds the power supplies, two pairs of crossing diodes D1 to D4 will prevent the output from reversing polarity. If the input voltage exceeds either power supply by 700mV, diode D1/D2 or D3/D4 will turn on to keep the output at the proper polarity. For the phase reversal protection to perform properly, the input current must be limited to less than 10mA. If the amplifier is severely overdriven, an external resistor should be used to limit the overdrive current.

The LT1800's input stages are also protected against a large differential input voltage of 1.4V or higher by a pair of back-back diodes D5/D8 to prevent the emitter-base breakdown of the input transistors. The current in these diodes should be limited to less than 10mA when they are active. The worst-case differential input voltage usually occurs when the input is driven while the output is shorted to ground in a unity gain configuration. In addition, the amplifier is protected against ESD strikes up to 3kV on all pins by a pair of protection diodes on each pin that are connected to the power supplies as shown in Figure 1.

Capacitive Load

The LT1800 is optimized for high bandwidth, low power and precision applications. It can drive a capacitive load of about 75pF in a unity gain configuration, and more for higher gain. When driving a larger capacitive load, a resistor of 10Ω to 50Ω should be connected between the output and the capacitive load to avoid ringing or oscillation. The feedback should still be taken from the output so that the resistor will isolate the capacitive load to ensure stability. Graphs on capacitive loads indicate the transient response of the amplifier when driving capacitive load with a specified series resistor.

APPLICATIONS INFORMATION

Feedback Components

When feedback resistors are used to set up gain, care must be taken to ensure that the pole formed by the feedback resistors and the total capacitance at the inverting input does not degrade stability. For instance, the LT1800 in a noninverting gain of 2, set up with two 5k resistors and a capacitance of 5pF (part plus PC board) will probably ring in transient response. The pole is formed at 12.7MHz that will reduce phase margin by 32 degrees when the crossover frequency of the amplifier is around 20MHz. A capacitor of 5pF or higher connected across the feedback resistor will eliminate any ringing or oscillation.

TYPICAL APPLICATIONS

Single Supply 1A Laser Driver Amplifier

The circuit in the front page of this data sheet shows the LT1800 used in a 1A laser driver application. One of the reasons the LT1800 is well suited to this control task is that its 2.3V operation ensures that it will be awake during power-up and operated before the circuit can otherwise cause significant current to flow in the 2.1V threshold laser diode. Driving the noninverting input of the LT1800 to a voltage V_{IN} will control the turning on of the high current NPN transistor, FMMT619 and the laser diode. A current equal to $V_{IN}/R1$ flows through the laser diode. The LT1800 low offset voltage and low input bias current allows it to control the current that flows through the laser diode precisely. The overall circuit is a 1A per volt V-to-I converter. Frequency compensation components R2 and C1 are selected for fast but zero-overshoot time domain response to avoid overcurrent conditions in the laser. The time domain response of this circuit, measured at R1 and given a 500mV 230ns input pulse, is also shown in the graphic on the front page. While the circuit is capable of 1A operation, the laser diode and the transistor are thermally limited due to power dissipation, so they must be operated at low duty cycles.

Fast 1A Current Sense Amplifier

A simple, fast current sense amplifier in Figure 2 is suitable for quickly responding to out-of-range currents. The circuit amplifies the voltage across the 0.1Ω sense resistor by a gain of 20, resulting in a conversion gain of 2V/A. The –3dB bandwidth of the circuit is 4MHz, and the uncertainty due to V_{OS} and I_B is less than 4mA. The minimum output voltage is 60mV, corresponding to 30mA. The large-signal response of the circuit is shown in Figure 3.




Figure 2. Fast 1A Current Sense




Figure 3. Current Sense Amplifier Large-Signal Response

TYPICAL APPLICATIONS

Single 3V Supply, 1MHz, 4th Order Butterworth Filter

The circuit shown in Figure 4 makes use of the low voltage operation and the wide bandwidth of the LT1800 to create a DC accurate 1MHz 4th order lowpass filter powered from a 3V supply. The amplifiers are configured in the inverting mode for the lowest distortion and the output can swing rail-to-rail for maximum dynamic range. Figure 5 displays the frequency response of the filter. Stopband attenuation is greater than 100dB at 50MHz. With a 2.25V_{P-P}, 250kHz input signal, the filter has harmonic distortion products of less than –85dBc. Worst-case output offset voltage is less than 6mV.




Figure 4. 3V, 1MHz, 4th Order Butterworth Filter





Figure 5. Frequency Response of Filter

PACKAGE DESCRIPTION


S5 Package
5-Lead Plastic TSOT-23
(Reference LTC DWG # 05-08-1635)



NOTE:
1. DIMENSIONS ARE IN MILLIMETERS
2. DRAWING NOT TO SCALE
3. DIMENSIONS ARE INCLUSIVE OF PLATING
4. DIMENSIONS ARE EXCLUSIVE OF MOLD FLASH AND METAL BURR
5. MOLD FLASH SHALL NOT EXCEED 0.254mm
6. JEDEC PACKAGE REFERENCE IS MO-193

PACKAGE DESCRIPTION

S8 Package
8-Lead Plastic Small Outline (Narrow .150 Inch)
(Reference LTC DWG # 05-08-1610)



NOTE:
1. DIMENSIONS IN $\frac{\text{INCHES}}{(\text{MILLIMETERS})}$
2. DRAWING NOT TO SCALE
3. THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.
   MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED .006" (0.15mm)

SO8 0303

Information furnished by Linear Technology Corporation is believed to be accurate and reliable. However, no responsibility is assumed for its use. Linear Technology Corporation makes no representation that the interconnection of its circuits as described herein will not infringe on existing patent rights.

TYPICAL APPLICATION

Low Power High Voltage Amplifier

Certain materials used in optical applications have characteristics that change due to the presence and strength of a DC electric field. The voltage applied across these materials should be precisely controlled to maintain desired properties, sometimes as high as 100's of volts. The materials are not conductive and represent a capacitive load.

The circuit of Figure 6 shows the LT1800 used in an amplifier capable of a 250V output swing and providing precise DC output voltage. When no signal is present, the op amp output sits at about mid-supply. Transistors Q1 and Q3 create bias voltages for Q2 and Q4, which are forced into a low quiescent current by degeneration resistors R4 and R5. When a transient signal arrives at V_{IN}, the op amp output moves and causes the current in Q2 or Q4 to change depending on the signal polarity. The current, limited by the clipping of the LT1800 output and the 3kΩ of total emitter degeneration, is mirrored to the output devices to drive the capacitive load. The LT1800 output then returns to near mid-supply, providing the precise DC output voltage to the load. The attention to limit the current of the output devices minimizes power dissipation thus allowing for dense layout, and inherits better reliability. Figure 7 shows the time domain response of the amplifier providing a 200V output swing into a 100pF load.




Figure 6. Low Power, High Voltage Amplifier




Figure 7. Large-Signal Time Domain Response of the Amplifier

RELATED PARTS

PART NUMBER	DESCRIPTION	COMMENTS
LT1399	Triple 300MHz Current Feedback Amplifier	0.1dB Gain Flatness to 150MHz, Shutdown
LT1498/LT1499	Dual/Quad 10MHz, 6Vµs Rail-to-Rail Input and Output C-Load™ Op Amps	High DC Accuracy, 475µV $V_{OS(MAX)}$, 4mV/°C Max Drift, Max Supply Current 2.2mA per Amp
LT1630/LT1631	Dual/Quad 30MHz, 10V/µs Rail-to-Rail Input and Output Op Amps	High DC Accuracy, 525µV $V_{OS(MAX)}$, 70mA Output Current, Max Supply Current 4.4mA per Amplifier
LT1801/LT1802	80MHz, 25V/µs Low Power Rail-to-Rail Input/Output Precision Op Amps	Dual/Quad Version of the LT1800
LT1806/LT1807	Single/Dual 325MHz, 140V/µs Rail-to-Rail Input and Output Op Amps	High DC Accuracy, 550µV $V_{OS(MAX)}$, Low Noise 3.5nV/√Hz, Low Distortion –80dB at 5MHz, Power-Down (LT1806)
LT1809/LT1810	Single/Dual 180MHz Rail-to-Rail Input/Output Op Amps	350V/µs Slew Rate, Low Distortion –t at 5MHz, Power-Down (LT1809)

C-Load is a trademark of Linear Technology Corporation.

Linear Technology Corporation
1630 McCarthy Blvd., Milpitas, CA 95035-7417
(408) 432-1900 • FAX: (408) 434-0507 • www.linear.com
LT 0709 REV A • PRINTED IN USA
© LINEAR TECHNOLOGY CORPORATION 2009

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Analog Devices Inc.:

LT1800CS5#TRMPBF LT1800IS5#TRPBF LT1800IS8#TRPBF LT1800IS8#PBF LT1800CS8#TRPBF LT1800CS8#PBF LT1800IS5#TRMPBF LT1800CS5#TRPBF