



NOTES:

1. DUST CAPS ARE NOT SHOWN.
2. LABEL IS PRINTED WITH SERIAL NUMBER. TEST DATA IS SENT WITH EACH SHIPMENT.
3. MAXIMUM INSERTION LOSS PER CONN./CHANNEL @850um: 0.5dB.

EC NO: MF2003-0731 DRWN: YBEDINYA2003/03/20 CHKD: IGUMIN 2003/03/20 APPR: IGUMIN 2003/03/21	DESCRIPTION REV A	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY															
		▽ = 0 ∇ = 0	<table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± .0002</td> </tr> <tr> <td>3 PLACES</td> <td>± 0.005</td> <td>± .005</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.13</td> <td>± .01</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.25</td> <td>± ---</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± ---	± .0002	3 PLACES	± 0.005	± .005	2 PLACES	± 0.13	± .01	1 PLACE	± 0.25	± ---	DIMENSION STYLE INCH ONLY DRAWN BY YGB DATE 3.12.03 CHECKED BY LK DATE 3.12.03	TITLE MPO TO SMC MM 50/125UM 12F RIBBON JUMPER		
			mm	INCH																		
		4 PLACES	± ---	± .0002																		
3 PLACES	± 0.005	± .005																				
2 PLACES	± 0.13	± .01																				
1 PLACE	± 0.25	± ---																				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			APPROVED BY ILG DATE 3.13.03	MOLEX INCORPORATED MATERIAL NO. 862824413 DOCUMENT NO. SD-86282-4413		SHEET NO. 1 OF 1																
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						B																