

M3H & MH Series

8 pin DIP, 3.3 or 5.0 Volt, HCMOS/TTL Clock Oscillator



- Standard 8 DIP Package
- 3.3 or 5.0 Volt Versions
- RoHS Compliant Version available (-R)
- Low Jitter
- Tristate Option
- Wide Operating Temperature Range

Ordering Information

00.0000
MHz

M3H / MH 1 3 F A D -R

Product Series _____
M3H = 3.3 Volt
MH = 5.0 Volt

Temperature Range _____
1: 0°C to +70°C 2: -40°C to +85°C
3: -55°C to +105°C 4: -55°C to +125°C
5: -10°C to +85°C 6: -20°C to +70°C
7: 0°C to +85°C

Stability _____
1: ±1000 ppm 2: ±500 ppm
3: ±100 ppm 4: ±50 ppm
5: ±35 ppm 6: ±25 ppm
*8: ±20 ppm

Output Type _____
F: Fixed T: Tristate


Symmetry/Logic Compatibility _____
A: 40/60 HCMOS/TTL B: 45/55 TTL (MH series only)
C: 45/55 HCMOS D: 45/55 HCMOS/TTL (MH to 50 MHz only)

Package/Lead Configurations _____
D: DIP; Nickel Header G: Gull Wing; Nickel Header

RoHS Compliance _____
Blank: non-RoHS compliant part
-R: RoHS compliant part

Frequency (customer specified) _____

*Contact factory for availability
M2004Sxxx & M2006Sxxx - Contact factory for datasheet.



Pin Connections

PIN	FUNCTION
1	N/C or Tristate
4	Circuit/Case Ground
5	Output
8	+Vdd

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	1.5		100	MHz	M3H
		1.0		80	MHz	MH
Operating Temperature	T _A	(See ordering information)				
Storage Temperature	T _S	-55		+125	°C	
Frequency Stability	ΔF/F	(See ordering information)				
Aging			±3		ppm	
1st Year			±2		ppm	
Thereafter (per year)						
Input Voltage	V _{dd}	3.135	3.3	3.465	V	M3H
		4.5	5.0	5.5	V	MH
Input Current (M3H)	I _{dd}			25	mA	1.5000 to 50.000 MHz
				35	mA	50.001 to 67.000 MHz
				55	mA	67.001 to 100.000 MHz
Input Current (MH)	I _{dd}			40	mA	1.000 to 40.000 MHz
				60	mA	40.001 to 80.000 MHz
Output Type						HCMOS/TTL
Load		2 TTL or 15 pF				M3H
		10 TTL or 50 pF				MH
						See Note 2
Symmetry (Duty Cycle)		(See ordering information)				
Logic "1" Level	V _{oh}	90% V _{dd}			V	HCMOS Load
		V _{dd} -0.5			V	TTL Load
Logic "0" Level	V _{ol}			10% V _{dd}	V	HCMOS Load
				0.5	V	TTL Load
Output Current				±4	mA	M3H
				±16	mA	MH
Rise/Fall Time	T _r /T _f			10	ns	See Note 4
Tristate Function		Input Logic "1" or floating: output active Input Logic "0": output disables to high-Z				
Start up Time				10	ms	
Random Jitter	R _j		5	12	ps RMS	1-Sigma
Environmental	Mechanical Shock	MIL-STD-202, Method 213, C (100 g's)				
	Vibration	MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)				
	Thermal Cycle	MIL-STD-883, Method 1010, B (-55°C to +125°C, 15 min dwell, 10 cycles)				
	Hermeticity	MIL-STD-202, Method 112				
	Solderability	Per EIAJ-STD-002				
	Max Wave Soldering Conditions	+260°C for 10 seconds				

1. Contact the factory for availability of higher frequencies.
2. TTL load - see Load Circuit Diagram #1. HCMOS load - see Load Circuit Diagram #2.
3. Symmetry is measured at 1.4 V with TTL load and at 50% V_{dd} with HCMOS load.
4. Rise/fall times are measured between 0.4 V and 2.4 V with TTL load, and between 10% V_{dd} and 90% V_{dd} with HCMOS Load.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.