

Partition plate - ATP-UT



3047167

<https://www.phoenixcontact.com/us/products/3047167>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Partition plate, length: 53.4 mm, width: 2.2 mm, height: 45.7 mm, color: gray



Partition plate - ATP-UT

3047167

<https://www.phoenixcontact.com/us/products/3047167>



Commercial Data

Item number	3047167
Packing unit	1 pc
Minimum order quantity	50 pc
Sales Key	B01
Product Key	BE1Z1X
Catalog Page	Page 26 (C-3-2013)
GTIN	4017918962159
Weight per Piece (including packing)	3.075 g
Weight per Piece (excluding packing)	2.936 g
Customs tariff number	39269097
Country of origin	DE

Partition plate - ATP-UT



3047167

<https://www.phoenixcontact.com/us/products/3047167>

Technical Data

Product properties

Product type	Partition plate
--------------	-----------------

Dimensions

Width	2.2 mm
Height	45.7 mm
Length	53.4 mm

Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Partition plate - ATP-UT

3047167

<https://www.phoenixcontact.com/us/products/3047167>



Classifications

ECLASS

ECLASS-10.0.1	27141133
ECLASS-9.0	27141133
ECLASS-11.0	27141133

ETIM

ETIM 8.0	EC000886
----------	----------

UNSPSC

UNSPSC 21.0	
-------------	--

Partition plate - ATP-UT



3047167
<https://www.phoenixcontact.com/us/products/3047167>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com