



Vishay Draloric

# **High Voltage Disc Capacitors, Screw mounting**

HPD, 20KV<sub>pc</sub>





· Dimensions in millimeters (inches)

CERAMIC	CAPACITANCE VALUE [pF]	RATED VOLTAGE*	RF - RATED CURRENT**	D1	D
	350	20KV <sub>DC</sub> or 15KV <sub>RMS</sub> up to 120Hz	6 A <sub>RMS</sub> max.	21 (0.827)	50 max. (1.969 max.)
R 2000 H	500			25 (0.984)	50 max. (1.969 max.)
	750			30 (1.181)	50 max. (1.969 max.)
	1000			35 (1.378)	50 max. (1.969 max.)
	1500			43 (1.693)	60 max. (2.362 max.)
	2000			49 (1.929)	60 max. (2.362 max.)
	3000			59 (2.323)	70 max. (2.756 max.)
	5000			75 (2.953)	90 max. (3.453 max.)

<sup>\*</sup> For model HPD these values apply only under conditions of high insulation, e.g. when operating under oil. When using the capacitors in free air, the rated voltage is reduced to 7KV<sub>DC</sub>.

#### **CAPACITANCE TOLERANCE:** ± 20%

#### **MATERIAL:**

Capacitor elements made from Class 1 or 2 ceramic dielectric with noble metal electrodes.

### FINISH:

Capacitor body completely lacquered (HPD model) or protected with silicone rubber (HPC model).

#### **MARKING:**

Capacitance value and tolerance, DRALORIC Logo

### **APPLICATION:**

High voltage capacitors made from Class 2 - ceramic dielectric can be used as coupling and bypass capacitors where low power ratings are required and larger capacitance changes with temperature can be tolerated.

ORDERING INFORMATION							
20KV <sub>DC</sub>	2000pF	± <b>20%</b>	R 2000 H				
RATED VOLTAGE	CAPACITANCE VALUE	TOLERANCE	CERAMIC				
	20KV <sub>DC</sub>	20KV <sub>DC</sub> 2000pF	20KV <sub>DC</sub> 2000pF ± 20%				

<sup>\*\*</sup> Max. ambient temperature + 60°C

## **Legal Disclaimer Notice**



Vishay

## **Notice**

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

www.vishay.com Revision: 08-Apr-05