


Metallized Polyester Film Capacitor

Related Document: IEC 60384-2

Dimensions in millimeters



MAIN APPLICATIONS

Blocking, bypassing, filtering, timing, coupling and decoupling circuits, interference suppression in low voltage applications.

MARKING

Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture

DIELECTRIC

Polyester film

ELECTRODES

Vacuum deposited aluminum

COATING

Flame retardant plastic case (class UL 94 V-0)

CONSTRUCTION

Extended metallized film

LEADS

Tinned wire

IEC TEST CLASSIFICATION

55/100/56, according to IEC 60068

TEMPERATURE RANGE

- 55 °C to + 100 °C

CAPACITANCE RANGE

1000 pF to 15 μ F

CAPACITANCE TOLERANCES

$\pm 20\%$ (M), $\pm 10\%$ (K), $\pm 5\%$ (J)

MAXIMUM PULSE RISE TIME dV/dt

PCM (mm)	Maximum Pulse Rise Time dV/dt [V/ μ s]					
	63 V _{DC}	100 V _{DC}	250 V _{DC}	400 V _{DC}	630 V _{DC}	1000 V _{DC}
10	11	13	22	37	60	130
15	7	8	13	21	33	65
22.5	4	5	8	13	19	34
27.5	3	4	6	10	14	25

Note

If the maximum pulse voltage is less than the rated voltage higher dV/dt values can be permitted.

FEATURES

- Compliant to RoHS directive 2002/95/EC

RATED VOLTAGES (U_R)

63 V_{DC}, 100 V_{DC}, 250 V_{DC}, 400 V_{DC}, 630 V_{DC}, 1000 V_{DC}

PERMISSIBLE AC VOLTAGES (RMS) UP TO 60 Hz

40 V_{AC}, 63 V_{AC}, 160 V_{AC}, 200 V_{AC}, 220 V_{AC}

TEST VOLTAGE (ELECTRODE/ELECTRODE)

1.6 x U_R for 2 s

INSULATION RESISTANCE

Measured at 100 V_{DC} (63 V_{DC} series measured at 50 V_{DC}) after one minute

For C \leq 0.33 μ F and U_R > 100 V_{DC}:

30 000 M Ω minimum value (100 000 M Ω typical value)

For C \leq 0.33 μ F and U_R \leq 100 V_{DC}:

15 000 M Ω minimum value (50 000 M Ω typical value)

TIME CONSTANT

Measured at 100 V_{DC} (63 V_{DC} series measured at 50 V_{DC}) after one minute

For C > 0.33 μ F and U_R > 100 V_{DC}:

10 000 s minimum value (40 000 s typical value)

For C > 0.33 μ F and U_R \leq 100 V_{DC}:

5000 s minimum value (15 000 s typical value)

CAPACITANCE DRIFT

Up to + 40 °C, $\pm 1.5\%$ for a period of two years

DERATING FOR DC AND AC CATEGORY VOLTAGE U_C

At + 85 °C: U_C = 1.0 U_R

At + 100 °C: U_C = 0.8 U_R

SELF INDUCTANCE

~ 6 nH measured with 2 mm long leads

PULL TEST ON LEADS

≥ 30 N in direction of leads according to IEC 60068-2-21

DISSIPATION FACTOR tan δ

MEASURED AT	C \leq 0.1 μ F	0.1 μ F < C \leq 1.0 μ F	C > 1.0 μ F
1 kHz	8 x 10 ⁻³	8 x 10 ⁻³	10 x 10 ⁻³
10 kHz	15 x 10 ⁻³	15 x 10 ⁻³	-
100 kHz	25 x 10 ⁻³	-	-
Maximum values			



RoHS
COMPLIANT

CAPACITANCE	CAPACITANCE CODE	VOLTAGE CODE 06 63 V _{DC} /40 V _{AC}				VOLTAGE CODE 01 100 V _{DC} /63 V _{AC}				VOLTAGE CODE 25 250 V _{DC} /160 V _{AC}			
		W	H	L	PCM	W	H	L	PCM	W	H	L	PCM
1000 pF	-210	-	-	-	-	-	-	-	-	-	-	-	-
1500 pF	-215	-	-	-	-	-	-	-	-	-	-	-	-
2200 pF	-222	-	-	-	-	-	-	-	-	-	-	-	-
3300 pF	-233	-	-	-	-	-	-	-	-	-	-	-	-
4700 pF	-247	-	-	-	-	-	-	-	-	-	-	-	-
6800 pF	-268	-	-	-	-	-	-	-	-	-	-	-	-
0.01 μF	-310	-	-	-	-	-	-	-	-	-	-	-	-
0.015 μF	-315	-	-	-	-	-	-	-	-	-	-	-	-
0.022 μF	-322	-	-	-	-	-	-	-	-	-	-	-	-
0.033 μF	-333	-	-	-	-	-	-	-	-	4.0	9.0	13.0	10
0.047 μF	-347	-	-	-	-	-	-	-	-	4.0	9.0	13.0	10
0.068 μF	-368	-	-	-	-	4.0	9.0	13.0	10	4.5	9.5	13.0	10
0.1 μF	-410	-	-	-	-	4.0	9.0	13.0	10	5.5	10.5	18.0	15
0.15 μF	-415	-	-	-	-	4.0	9.0	13.0	10	5.5	10.5	18.0	15
0.22 μF	-422	4.0	9.0	13.0	10	4.5	9.5	13.0	10	5.5	10.5	18.0	15
0.33 μF	-433	4.0	9.0	13.0	10	5.5	10.5	18.0	15	6.5	12.5	18.0	15
0.47 μF	-447	5.5	10.5	13.0	10	5.5	10.5	18.0	15	6.5	14.5	26.5	22.5
0.68 μF	-468	5.5	10.5	18.0	15	6.5	12.5	18.0	15	7.5	15.5	26.5	22.5
1.0 μF	-510	5.5	10.5	18.0	15	7.5	13.5	18.0	15	8.5	16.5	26.5	22.5
1.5 μF	-515	6.5	12.5	18.0	15	7.5	15.5	26.5	22.5	9.0	18.5	31.5	27.5
2.2 μF	-522	7.5	13.5	18.0	15	8.5	16.5	26.5	22.5	11.5	20.5	31.5	27.5
3.3 μF	-533	7.5	15.5	26.5	22.5	10.5	18.5	26.5	22.5	13.5	23.5	31.5	27.5
4.7 μF	-547	8.5	16.5	26.5	22.5	11.5	20.5	31.5	27.5	-	-	-	-
6.8 μF	-568	10.5	18.5	26.5	22.5	13.5	23.5	31.5	27.5	-	-	-	-
10.0 μF	-610	11.5	20.5	31.5	27.5	15.0	24.5	31.5	27.5	-	-	-	-
15.0 μF	-615	13.5	23.5	31.5	27.5	16.5	29.5	31.5	27.5	-	-	-	-

RECOMMENDED PACKAGING

LETTER CODE	TYPE OF PACKAGING	HEIGHT (H) (mm)	REEL DIAMETER (mm)	ORDERING CODE EXAMPLES	PCM 10	PCM 15	PCM 22.5 to 27.5
D	Ammo	16.5	S ⁽¹⁾	MKT 1822-422-065-D	X	X	-
G	Ammo	18.5	S ⁽¹⁾	MKT 1822-422-065-G	X	X	-
F	Reel	16.5	350	MKT 1822-422-065-F	X	X	-
W	Reel	18.5	350	MKT 1822-422-065-W	X	X	-
V	Reel	18.5	500	MKT 1822-510-255-V	-	X	X
G	Ammo	18.5	L ⁽²⁾	MKT 1822-510-255-G	-	-	X
-	Bulk	-	-	MKT 1822-510-255	X	X	X

Notes⁽¹⁾ S = box size 55 mm x 210 mm x 340 mm (W x H x L)⁽²⁾ L = box size 60 mm x 360 mm x 510 mm (W x H x L)



CAPACITANCE	CAPACITANCE CODE	VOLTAGE CODE 40 400 V _{DC} /200 V _{AC}				VOLTAGE CODE 63* 630 V _{DC} /220 V _{AC}				VOLTAGE CODE 10* 1000 V _{DC} /220 V _{AC}			
		W	H	L	PCM	W	H	L	PCM	W	H	L	PCM
1000 pF	-210	4.0	9.0	13.0	10	4.0	9.0	13.0	10	4.0	9.0	13.0	10
1500 pF	-215	4.0	9.0	13.0	10	4.0	9.0	13.0	10	4.0	9.0	13.0	10
2200 pF	-222	4.0	9.0	13.0	10	4.0	9.0	13.0	10	4.0	9.0	13.0	10
3300 pF	-233	4.0	9.0	13.0	10	4.0	9.0	13.0	10	4.0	9.0	13.0	10
4700 pF	-247	4.0	9.0	13.0	10	4.0	9.0	13.0	10	5.5	10.5	13.0	10
6800 pF	-268	4.0	9.0	13.0	10	4.0	9.0	13.0	10	6.5	11.5	13.0	10
0.01 µF	-310	4.0	9.0	13.0	10	4.0	9.0	13.0	10	5.5	10.5	18.0	15
0.015 µF	-315	4.0	9.0	13.0	10	5.5	10.5	13.0	10	6.5	12.5	18.0	15
0.022 µF	-322	4.0	9.0	13.0	10	6.5	11.5	13.0	10	7.5	13.5	18.0	15
0.033 µF	-333	4.0	9.0	13.0	10	5.5	10.5	18.0	15	6.5	14.5	26.5	22.5
0.047 µF	-347	5.5	10.5	18.0	15	6.5	12.5	18.0	15	7.5	15.5	26.5	22.5
0.068 µF	-368	5.5	10.5	18.0	15	7.5	13.5	18.0	15	8.5	16.5	26.5	22.5
0.1 µF	-410	5.5	10.5	18.0	15	6.5	14.5	26.5	22.5	10.5	18.5	26.5	22.5
0.15 µF	-415	6.5	12.5	18.0	15	7.5	15.5	26.5	22.5	11.5	20.5	31.5	27.5
0.22 µF	-422	7.5	15.5	26.5	22.5	8.5	16.5	26.5	22.5	13.5	23.5	31.5	27.5
0.33 µF	-433	8.5	16.5	26.5	22.5	11.5	20.5	31.5	27.5	16.5	29.5	31.5	27.5
0.47 µF	-447	10.5	18.5	26.5	22.5	11.5	20.5	31.5	27.5	20.0	35.0	31.5	27.5
0.68 µF	-468	11.5	20.5	31.5	27.5	13.5	23.5	31.5	27.5	-	-	-	-
1.0 µF	-510	11.5	20.5	31.5	27.5	15.0	24.5	31.5	27.5	-	-	-	-
1.5 µF	-515	13.5	23.5	31.5	27.5	-	-	-	-	-	-	-	-
2.2 µF	-522	-	-	-	-	-	-	-	-	-	-	-	-
3.3 µF	-533	-	-	-	-	-	-	-	-	-	-	-	-
4.7 µF	-547	-	-	-	-	-	-	-	-	-	-	-	-
6.8 µF	-568	-	-	-	-	-	-	-	-	-	-	-	-
10.0 µF	-610	-	-	-	-	-	-	-	-	-	-	-	-
15.0 µF	-615	-	-	-	-	-	-	-	-	-	-	-	-

Notes

• Further C-values upon request.

* Not suitable for mains applications.

Please refer to X-capacitors in our catalog “RFI Suppression Components”


RECOMMENDED PACKAGING

LETTER CODE	TYPE OF PACKAGING	HEIGHT (H) (mm)	REEL DIAMETER (mm)	ORDERING CODE EXAMPLES	PCM 10	PCM 15	PCM 22.5 to 27.5
D	Ammo	16.5	S ⁽¹⁾	MKT 1822-422-065-D	X	X	-
G	Ammo	18.5	S ⁽¹⁾	MKT 1822-422-065-G	X	X	-
F	Reel	16.5	350	MKT 1822-422-065-F	X	X	-
W	Reel	18.5	350	MKT 1822-422-065-W	X	X	-
V	Reel	18.5	500	MKT 1822-510-255-V	-	X	X
G	Ammo	18.5	L ⁽²⁾	MKT 1822-510-255-G	-	-	X
-	Bulk	-	-	MKT 1822-522-255	X	-	X


Notes

⁽¹⁾ S = box size 55 mm x 210 mm x 340 mm (W x H x L)


⁽²⁾ L = box size 60 mm x 360 mm x 510 mm (W x H x L)




Permissible AC Voltage versus Frequency




Permissible AC Voltage versus Frequency




Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Permissible AC Voltage versus Frequency



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.